

Construction of Minimal Tail-Biting Trellises for Codes over Finite Abelian Groups

Qinqin Yang and Zhongping Qin

Abstract—A definition of atomic codeword for a group code is presented. Some properties of atomic codewords of group codes are investigated. Using these properties, it is shown that every minimal tail-biting trellis for a group code over a finite abelian group can be constructed from its characteristic generators, which extends the work of Koetter and Vardy who treated the case of a linear code over a field. We also present an efficient algorithm for constructing the minimal tail-biting trellis of a group code over a finite abelian group, given a generator matrix.

Index Terms—atomic codewords, biproper p -bases, characteristic generators, group codes, tail-biting trellises.

I. INTRODUCTION

TRELLIS representations of block codes not only illuminate code structure, but also provide a general framework for efficient soft-decision decoding of codes [1]–[5], for instance by using the Viterbi algorithm [6]. Since the decoding effort is directly related to the complexity of the trellis, such as the vertex-class profile, the edge-class profile and the overall Viterbi decoding complexity [7]–[9], characterizing and constructing minimal trellises for block codes are important in trellis theory [10]–[22]. It is well known [16]–[18] that for any linear code over a field or group code, there exists a unique minimal conventional trellis up to isomorphism. Furthermore, the minimal conventional trellis for any linear code over a field can be easily constructed from its generator matrix or parity check matrix by several methods [15] and [19]. In [20], the authors proved that the minimal trellis for a group code over a finite abelian group is the product of some minimal trellises for linear codes over Z_{p^α} , then for arbitrary finite abelian group, it is sufficient to consider a linear code over a ring Z_{p^α} . By the method, they generalized the result in [15] into codes over finite abelian groups and proved that the minimal conventional trellis for any group code can be easily constructed from its biproper p -basis. A tail-biting trellis may be has less complexity than the minimal conventional trellis for the code, [23] and [24]. However, much less is known about efficient construction of tail-biting trellises. The authors in [12] proved that any linear tail-biting trellis for a linear code over a field can be constructed from its characteristic generators, and conjectured that it is correct for a group code over a finite abelian group. In [25], the authors presented the difficulty when they try to prove the conjecture in [12].

In this paper, our goal is to show that the conjecture in [12] is true and present an algorithm for constructing the minimal tail-biting trellis of a group code over a finite abelian group, given a generator matrix. A key step toward proving the conjecture is handling codes over cyclic groups C_{p^α} . Such a code can be viewed as a linear code over ring Z_{p^α} . Because the order of p -generator sequence, p -bases of a linear code over Z_{p^α} do not share the useful properties of a basis of a linear code over a field. We get around this difficulty by introducing the notion of atomic codeword of a linear code over Z_{p^α} , which enjoys properties similar to those of atomic codeword for a linear code over a field.

We start with the definitions of conventional and tail-biting trellises in section II. We then introduce a number of concepts related to tail-biting trellises. It follows from [20] that the problem of constructing minimal tail-biting trellises of a block code over a finite abelian group reduces to the case of linear codes over ring Z_{p^α} . Thus, we introduce the concepts of p -generator sequences and p -linear combinations of a linear code over Z_{p^α} .

In section III, we present a rigorous definition of atomic codeword for a group code. Some properties of atomic codewords of group codes are investigated. It is well known in [15] that minimal conventional trellises for linear codes over fields are obtained by forming the product of elementary trellises corresponding to the one-dimensional subcodes generated by atomic codewords and the structure of the trellis is determined solely by the spans of the atomic codewords. These spans, called atomic spans, are uniquely determined by the linear code over a field. Furthermore, any set of k codewords of the linear code of dimension k over a field with atomic spans is a basis in minimal-span form. Any two bases in minimal-span form give the same set of conventional spans, although a basis in minimal-span form is not unique. We can find a biproper p -basis of a linear code over Z_{p^α} shares the useful properties of a basis in minimal-span form of a linear code over a field. This make us to define a definition of atomic codeword for a group code and it is possible to extend the work of Koetter and Vardy.

In section IV, using these properties of atomic codewords of group codes, we show the conjecture in [12] is true. We also proved that the conjecture in [12] is true under other minimality orders for tail-biting trellis. Therefore, we show that although minimal tail-biting trellises for group codes are generally not unique, every minimal linear tail-biting trellis for a group code over a finite abelian group necessarily can be construct from its characteristic matrix. This gives a general solution to the problem of constructing minimal linear tail-

Manuscript received February 3, 2007; revised ... This work was supported by the National Science Foundation of China under Grant 10571067.

Q. Yang is with the Department of Computer Science, Wuhan University, Wuhan, 430072, China (e-mail: yqq-wuda@163.com).

Z. Qin is with the Department of Software, Huazhong University of Science and Technology, Wuhan, 430079, China (e-mail: zpqin0001@126.com).

biting trellises for group codes over finite abelian groups.

In section V, we consider codes over finite abelian groups. Since a code over a finite abelian group can be decomposed into a direct product of codes over those abelian p -groups which are all Sylow p -subgroup of the group and a code of length n over p -group is equivalent to a linear code of length mn over Z_{p^α} , for arbitrary finite abelian group, it is sufficient to consider the case of a linear code over a ring Z_{p^α} . Therefore, we present an algorithm for computing this characteristic matrix in time $O(n^3)$ from any p -basis for a linear code over a ring Z_{p^α} . For arbitrary finite abelian group, using sectionalization, we can obtain a minimal linear tail-biting trellis for a code over the group from minimal linear tail-biting trellises for linear codes over Z_{p^α} , which is similar to the method in [20]. Thus we get an efficient algorithm for constructing the minimal tail-biting trellis of a group code over a finite abelian group, given a generator matrix.

The research on trellises for lattices is also an important topic. The problem of constructing minimal trellises is still open. Since this problem essentially reduces to that of constructing minimal trellises for block codes over abelian groups, [26] and [27], the most important application of our work is to the construction of minimal trellises for lattices. In [28], the authors proved that under the Gray map from $(Z_2)^2$ to the ring Z_4 , these codes are linear over Z_4 , or equivalently, are group codes over C_4 . Therefore, another application is to the construction of minimal trellises for some famous nonlinear binary codes, including Kerdock, Preparata, and Goethals codes.

II. PRELIMINARIES

In this section, We first introduce some definitions that will be used in the paper, see also [29].

Let G be a finite abelian group. A subgroup C of G^n under the componentwise addition operation of G is said to be a *group code over G* . Let R be a ring. C is a *linear code over R* if C is a subgroup of R^n under the componentwise addition operation of R and C is closed under componentwise multiplication with elements of R . In fact, a linear code C over R is exactly a submodule of R^n . When $R = F_q$, a finite field, then C is a linear code over F_q . Clearly, the class of linear codes over fields is contained in the class of linear codes over rings, which is in turn contained in the class of group codes.

Now we introduce some basic concepts on conventional and tail-biting trellises.

An edge-labeled directed graph is a triple (V, E, A) , consisting of a set V of vertices, a finite set A called the alphabet, and a set E of ordered triples (v, a, v') , with $v, v' \in V$ and $a \in A$ called edges. We say that an edge $(v, a, v') \in E$ begins at v , ends at v' , and has label a .

Definition 2.1: A *conventional trellis* $T = (V, E, A)$ of length n is an edge-labeled directed graph with the following property: the vertex set V can be partitioned as

$$V = V_0 \cup V_1 \cup \cdots \cup V_n \quad (1)$$

where $|V_0| = |V_n| = 1$, such that every edge in T begins at a vertex of V_i and ends at a vertex of V_{i+1} , for some

$i = 0, 1, \dots, n-1$. The ordered index set $\mathcal{I} = \{0, 1, \dots, n\}$ induced by the partition in (1) is called the *time axis* for T .

The trellis T is *reduced* if every vertex in T lies on at least one path from a vertex in V_0 to a vertex in V_n . The trellis T said to *represent* a block code C of length n over A if C is precisely the set of all edge-labeled sequences corresponding to those paths in T that start at a vertex of V_0 .

In the following, we will see that tail-biting trellises may be viewed as a generalization of a conventional trellis to a circular time axis.

Definition 2.2: A *tail-biting trellis* $T = (V, E, A)$ of length n is an edge-labeled directed graph with the following property: the vertex set V can be partitioned as

$$V = V_0 \cup V_1 \cup \cdots \cup V_{n-1} \quad (2)$$

such that every edge in T begins at a vertex of V_i and ends at a vertex of V_{i+1} , for some $i = 0, 1, \dots, n-2$, or begins at a vertex of V_{n-1} and ends at a vertex of V_0 . The ordered index set $\mathcal{I} = \{0, 1, \dots, n-1\}$ induced by the partition in (2) is called the *time axis* for T .

An index interval $[i, j]$ represents the sequence $\{i, i+1, \dots, j\}$ if $i \leq j$, and the sequence $\{i, i+1, \dots, n-1, 0, \dots, j\}$ if $i > j$. Such interval $[i, j]$ is called *closed cycle interval*, we let semiopen cyclic interval $(i, j]$ denote $[i, j] \setminus \{i\}$. The tail-biting trellis T is *reduced* if every vertex in T lies on at least one cycle from a vertex in V_0 to a vertex in V_n . The tail-biting trellis T said to *represent* a block code C of length n over A if C is precisely the set of all edge-labeled sequences corresponding to those cycles in T that start at a vertex of V_0 .

Let $C(T)$ denote the code represented by a trellis T , either conventional or tail-biting. Let $T = (V, E, A)$ be a trellis, either conventional or tail-biting, of length n . The ordered sequence

$$\Theta(T) = (|V_0|, |V_1|, \dots, |V_{n-1}|)$$

is called the *vertex-class profile* of T . For a given code C , we say that a trellis T is less than or equal to another trellis T' , denoted as $T \preceq_\Theta T'$, if

$$|V_i| \leq |V'_i|, \text{ for all } i = 0, 1, \dots, n-1 \quad (3)$$

If there is at least a strict inequality, then T is strictly less than T' and write $T \prec_\Theta T'$.

Definition 2.3: A trellis T , either conventional or tail-biting, for a code C of length n is *minimal under $\prec_\Theta$* , or simply *minimal*, if there does not exist a trellis T' such that $T' \prec_\Theta T$.

It follows from [16], [17] and [20] that for linear or group codes there exists a unique minimal conventional trellis under $\prec_\Theta$ up to graph isomorphism. The unique minimal trellis has the smallest possible vertex count simultaneously at all times and minimizes all conceivable measures of trellis complexity

[18]. But there are many incomparable minimal tail-biting trellises under $\prec_\Theta$ up to graph isomorphism.

Now we introduce several total orders under which any two trellises are comparable. In the following, we let E_i denote the set of edges that start in a vertex of V_i and end in a vertex of V_{i+1} .

$$\textbf{product order: } T \preceq_\Pi T' \text{ if } \prod_{i=0}^{n-1} |V_i| \leq \prod_{i=0}^{n-1} |V'_i| \quad (4)$$

$$\textbf{max order: } T \preceq_{\max} T' \text{ if } \max_i |V_i| \leq \max_i |V'_i| \quad (5)$$

$$\textbf{vertex-sum order: } T \preceq_\Sigma T' \text{ if } \sum_{i=0}^{n-1} |V_i| \leq \sum_{i=0}^{n-1} |V'_i| \quad (6)$$

$$\textbf{edge-product order: } T \preceq_{\Pi\mathcal{E}} T' \text{ if } \prod_{i=0}^{n-1} |E_i| \leq \prod_{i=0}^{n-1} |E'_i| \quad (7)$$

$$\textbf{edge-max order: } T \preceq_{\max\mathcal{E}} T' \text{ if } \max_i |E_i| \leq \max_i |E'_i| \quad (8)$$

$$\textbf{edge-sum order: } T \preceq_{\Sigma\mathcal{E}} T' \text{ if } \sum_{i=0}^{n-1} |E_i| \leq \sum_{i=0}^{n-1} |E'_i| \quad (9)$$

It is obvious that if $T \preceq_\Theta T'$ implies that $T \preceq_\Pi T'$, $T \preceq_{\max} T'$ and $T \preceq_\Sigma T'$. Then the set of $\preceq_\Pi$ -minimal trellises, the set of $\preceq_{\max}$ -minimal trellises and the set of $\preceq_\Sigma$ -minimal trellises for a given code are subsets of the set of $\preceq_\Theta$ -minimal trellises for the same code. On the other hand, the set of $\preceq_{\Pi\mathcal{E}}$ -minimal linear trellises for a given code are subsets of the set of $\preceq_\Theta$ -minimal linear trellises for the same code. But this is not true for the edge-max order or the edge-sum order, see [12].

Definition 2.4: Let $T' = (V', E', A)$ and $T'' = (V'', E'', A)$ be two trellises of length n , either conventional or tail-biting, over the alphabet A , and assume that A is endowed with an associative addition operation. Then the *product trellis* $T' \times T''$ is the trellis $T = (V, E, A)$ whose vertex classes and edge classes are the Cartesian products, defined as follows:

$$V_i = \{(v', v'') : v' \in V'_i \text{ and } v'' \in V''_i\} \quad (10)$$

$$E_i = \{((v'_1, v''_1), a' + a'', (v'_2, v''_2)) : (v'_1, a', v'_2) \in E'_i \text{ and } (v''_1, a'', v''_2) \in E''_i\}. \quad (11)$$

There is an edge $e \in E_i$ in T labeled a , from a vertex $(v'_1, v''_1) \in V_{i-1}$ to a vertex $(v'_2, v''_2) \in V_i$ if and only if $(v'_1, a', v'_2) \in E'_i$, $(v''_1, a'', v''_2) \in E''_i$ and $a = a' + a''$. If $C_1 = C(T')$ and $C_2 = C(T'')$, then the product trellis $T = T' \times T''$ represents the code

$$C_1 + C_2 = \{c_1 + c_2 : c_1 \in C_1, c_2 \in C_2\}. \quad (12)$$

Clearly, the trellis product operator is both associative and commutative.

Notice that in the paper, a trellis is either conventional or tail-biting. We will see that the notion of a trellis product and the corresponding product construction are very important for constructing minimal trellises, see also [12-16] and [18]-[21].

If C is a linear code of length n and dimension k over the field F_q , let $\{x_1, x_2, \dots, x_k\}$ be a basis for C and let

$\langle x_i \rangle$ denote the one-dimensional subcode of C generated by x_i . Then $C = \langle x_1 \rangle + \langle x_2 \rangle + \dots + \langle x_k \rangle$. If $T_1, T_2, \dots, T_k$ are trellises for $\langle x_1 \rangle, \langle x_2 \rangle, \dots, \langle x_k \rangle$, respectively, then their product $T = T_1 \times T_2 \times \dots \times T_k$ represents C . This completes the description of the product construction if we can specify the trellises $T_1, T_2, \dots, T_k$.

Now we introduce the notions of span and elementary trellis. Given a codeword $x \in C$, a *span* of x , denote $[x]$, is a semiopen interval $(i, j] \in \mathcal{I}$ such that the corresponding closed interval $[i, j]$ contains all the nonzero positions of x . We also allow $[x] = \mathcal{I}$. For a codeword x with span $(i, j]$, an *elementary trellis* of x , denote T_x , is the minimal trellis for $\langle x \rangle$ which is a one-dimensional code generated by x .

Given a codeword $x = (x_0, x_1, \dots, x_{n-1})$ over the field F_q , along with its span $[x] = (a, b]$, the corresponding elementary trellis T_x can be constructed as follows: T_x has q vertices labeled by the elements of F_q at times $a+1, \dots, b$, and a single vertex 0, at other positions. There is an edge $e \in E_i$ from a vertex $v \in V_i$ to a vertex $v' \in V_{i+1}$ if and only if $i = a$, or $i = b$, or the two vertices v, v' have the same label. All the edge-label sequences in T_x are the q different multiples of x . Note that an elementary trellis T_x depends not only on x and span $(a, b]$, but also on the ambient field F_q .

Similarly, for a codeword x of a group code, along with its span $[x] = (a, b]$ and its order q , the corresponding elementary trellis T_x can be constructed as follows: T_x has q vertices labeled by the elements of group $\langle x \rangle$ at times $a+1, \dots, b$, and a single vertex 0, at other positions. There is an edge $e \in E_i$ from a vertex $v \in V_i$ to a vertex $v' \in V_{i+1}$ if and only if $i = a$, or $i = b$, or the two vertices v, v' have the same label. All the edge-label sequences in T_x are the q different multiples of x .

From now on, we search for a solution to the problem of constructing minimal tail-biting trellises of a block code over a finite abelian group. It follows from [20] that the minimal trellis for group code C over a finite abelian group is the product of some minimal trellises for linear codes over Z_{p^α} . Thus we focus on our discussion on linear codes over Z_{p^α} .

Now we will introduce a number of concepts related to linear codes over Z_{p^α} . Let $V = \{x_1, x_2, \dots, x_k\}$ be a set of codewords of a linear code C over Z_{p^α} . $\sum_{i=1}^k a_i x_i$ is a *p-linear combination* of these codewords if all coefficients $a_i \in Z_p$.

Denoted by $p\text{-span}(V)$ the set of all elements generated by p -linear combination of the elements in V . An ordered sequence of $\{x_1, x_2, \dots, x_k\}$ over Z_{p^α} is said to be a *p-generator sequence* if for $1 \leq i \leq k$, px_i is a p -linear combination of the codewords $x_{i+1}, \dots, x_k$ (in particular, $px_k = 0$). For any p -generator sequence V , it was proved that $p\text{-span}(V) = \text{span}(V)$ and that the codeword 0 is a nontrivial p -linear combination of these codewords in V if and only if there is a codeword in V that can be expressed as a p -linear combination of the remaining codewords in V . A p -generator sequence V is *p-linearly independent* if the codeword 0 can not be expressed as a nontrivial p -linear combination of these codewords in V . A p -linearly independent p -generator sequence V is called a *p-basis of p-span(V)*. Obviously, the p -linear combination of the codewords of p -basis V uniquely generate the elements

of the module $p\text{-span}(V)$. If $|V| = k$, then the module has p^k elements and we say that the p -dimension of the module is k . We say that u and v in Z_{p^α} are associates if there exists a unit w in Z_{p^α} such that $u = wv$. Then u and v are associates if and only if they have the same order. A p -generator sequence V is *proper* if for any two codewords $u, v \in V$, either u and v start at different positions, or they start the same position but their starting components are not associates. Similarly, a p -generator sequence V is *coproper* if for any two codewords $u, v \in V$, either u and v end at different positions, or they end at the same position but their ending components are not associates. A p -generator sequence V is *biproper* if it is proper and coproper. A proper p -generator sequence $V = \{x_1, x_2, \dots, x_k\}$ is in *row echelon form* if for $1 \leq i < j \leq k$, either v_i has an earlier starting position than v_j , or v_i and v_j have the same starting position but the starting component of v_i has higher order than the starting component of v_j . By Theorem 6.12 and Lemma 7.1 in [20], we can get a proper p -generator sequence in row echelon form from any p -generator sequence and a biproper p -basis in row echelon form from any proper p -generator sequence in row echelon form. Any submodule of $Z_{p^\alpha}^n$ has a biproper p -basis by Theorem 6.11 in [20].

Therefore, for a codeword x over Z_{p^α} , along with its span $\langle x \rangle = (a, b]$, an elementary trellis of x over Z_{p^α} , denote T_x , is the minimal trellis for $p\text{-span}(\{x\})$ and can be constructed as follows: T_x has p vertices labeled by the elements of Z_p at times $a+1, \dots, b$, and a single vertex 0, at other positions. There is an edge $e \in E_i$ from a vertex $v \in V_i$ to a vertex $v' \in V_{i+1}$ if and only if $i = a$, or $i = b$, or the two vertices v, v' have the same label. All the edge-label sequences in T_x are the p different multiples of x . Let the order of x is p^r . The minimal trellis T for $\langle x \rangle$ which is a cyclic code generated by x over Z_{p^α} and can be constructed as $T = T_x \times T_{px} \times \dots \times T_{p^{r-1}x}$.

III. SOME RESULTS ON ATOMIC CLASSES

In this section, we present a definition of atomic codeword for a linear code over Z_{p^α} , which is a generalization of the notion of atomic codeword of a linear code over F_q , and study their basic structural properties.

For a codeword $x = (x_0, x_1, \dots, x_n) \in C$, we let $\triangleleft(x)$ denote the smallest integer i such that $x_i \neq 0$, $\triangleright(x)$ denote the largest integer j such that $x_j \neq 0$, and $o_1(x)$ and $o_2(x)$ denote the orders of the first and last nonzero components of x , respectively. We say that $(\triangleleft(x), \triangleright(x))$ is the *conventional span* of x and $((\triangleleft(x), \triangleright(x)), o_1(x), o_2(x))$ is a *characteristic triple* of x . The *span length* of x is defined as $\triangleright(x) - \triangleleft(x) + 1$. In the following, We will use the concept of characteristic triple of codeword to define an equivalence relation on any linear code C over Z_{p^α} .

Definition 3.1: Two codewords of a linear code C over Z_{p^α} are *equivalent* if and only if they have the same characteristic triple. An *atomic class* of a linear code C over Z_{p^α} is an equivalence class that their elements cannot be expressed as p -linear combinations of codewords from C of strictly smaller span lengths or p -linear combinations of a codeword having

strictly smaller span length and a codeword having the same conventional span and strictly smaller order of the first or the last nonzero component. The elements of an atomic class are called *atomic codewords*.

Remark 3.1: Obviously, any multiple of an atomic codeword by a unit in Z_{p^α} is also an atomic codeword with the same characteristic triple; however, an atomic class may consist of multiples of more than one codeword by units in Z_{p^α} . Note that the elements of a biproper p -basis of a linear code over Z_{p^α} are also atomic codewords.

For a field F_q , the order of any nonzero element in the addition group of F_q is the character of F_q . Thus, the above definition is a generalization of the definition of atomic codeword of a linear code over F_q .

In the following, we investigate some properties of atomic codewords.

Theorem 3.1: If c_1 and c_2 are atomic codewords in linear code C over Z_{p^α} and $(\triangleleft(c_1), o_1(c_1)) \neq (\triangleleft(c_2), o_1(c_2))$ or $(\triangleright(c_1), o_2(c_1)) \neq (\triangleright(c_2), o_2(c_2))$, then $(\triangleleft(c_1), o_1(c_1)) \neq (\triangleleft(c_2), o_1(c_2))$ and $(\triangleright(c_1), o_2(c_1)) \neq (\triangleright(c_2), o_2(c_2))$.

Proof: Suppose that for c_1 and c_2 , $(\triangleleft(c_1), o_1(c_1)) = (\triangleleft(c_2), o_1(c_2))$ and $(\triangleright(c_1), o_2(c_1)) \neq (\triangleright(c_2), o_2(c_2))$. Then $\triangleright(c_1) \neq \triangleright(c_2)$ or $\triangleright(c_1) = \triangleright(c_2)$ and $o_2(c_1) \neq o_2(c_2)$. Without loss of generality, let $\triangleright(c_1) < \triangleright(c_2)$ or $\triangleright(c_1) = \triangleright(c_2)$ and $o_2(c_1) < o_2(c_2)$. Then there exists a unit α in Z_{p^α} such that $c_3 = c_2 - \alpha c_1$ starts later than c_2 . Clearly, αc_1 is also an atomic codeword with the same characteristic triple as c_1 . Now $c_2 = c_3 + \alpha c_1$, therefore c_2 can be expressed as a p -linear combination of a codeword c_3 of strictly smaller span length and a codeword αc_1 having either strictly smaller span length or the same conventional span and strictly smaller order of the last nonzero component, contradicting the assumption that c_2 is atomic. The case in which the codewords have $(\triangleleft(c_1), o_1(c_1)) \neq (\triangleleft(c_2), o_1(c_2))$ and $(\triangleright(c_1), o_2(c_1)) = (\triangleright(c_2), o_2(c_2))$ is proved similarly. ■

Theorem 3.2: Let C be a linear code of length n and p -dimension k over Z_{p^α} . Then the elements of any set A of atomic codewords with the property that no two members of A belong to the same atomic class are p -linearly independent.

Proof: Any set of codewords, no two of which have the same starting position and order of the first nonzero component, are p -linearly independent and the elements of A have this property. ■

Theorem 3.3: Let C be a linear code of length n and p -dimension k over Z_{p^α} . Then every codeword c in C can be expressed as a p -linear combination of atomic codewords, each from a different atomic class. Moreover, a complete set of atomic class representatives in row echelon form is a biproper p -basis for C in row echelon form. Therefore, code C has k distinct atomic classes.

Proof: It is trivial if c is atomic. Now suppose c is not atomic, then c can be expressed as a p -linear combination of codewords from C of strictly smaller span lengths or a p -linear combination of a codeword having strictly smaller span length and a codeword having the same conventional span and strictly

smaller order of the first or the last nonzero component. Any combination of two codewords having the same characteristic triple may be replaced by either a single codeword with the same characteristic triple, or a codeword of strictly smaller span length. If any terms in this combination are themselves not atomic, then they can be further expressed a p -linear combination of codewords of strictly smaller span lengths or a p -linear combination of a codeword having strictly smaller span length and a codeword having the same conventional span and strictly smaller order of the first or the last nonzero component. Continuing in this way, we obtain a chain of strictly decreasing nonnegative span lengths, which is bound to terminate in finite steps, with the result that c is expressed as a p -linear combination of atomic codewords, no two from the same atomic class. Let $\{x_1, x_2, \dots, x_m\}$ be a complete set of atomic class representatives in row echelon form. We will show that $\{x_1, x_2, \dots, x_m\}$ is a p -generator sequence. For $1 \leq i \leq m$, px_i is a codeword starting later than x_i or having the same starting position as x_i and strictly smaller order of the first nonzero component than x_i , then px_i is expressed as a p -linear combination of atomic codewords $x_{i+1}, \dots, x_m$ (in particular, $px_m = 0$). By Theorem 3.1 and Theorem 3.2, $\{x_1, x_2, \dots, x_m\}$ is a biproper p -basis for C in row echelon form. Therefore, $m = k$ and code C has k distinct atomic classes. ■

In general, for a linear code C over Z_{p^α} , a biproper p -basis in row echelon form is not unique. However, by Theorem 3.3 and Remark 3.1, we have the following.

Corollary 3.1: Any two biproper p -bases in row echelon form have the same set of conventional spans and orders of the first and last nonzero components of the elements of biproper p -basis, which are uniquely determined by C .

Theorem 3.4: Let C be a linear code of length n and p -dimension k over Z_{p^α} . Then any codeword c with the same characteristic triple as an atomic codeword a is atomic.

Proof: If c were not atomic, c could be expressed as a p -linear combination of atomic codewords strictly smaller span lengths or a p -linear combination of atomic codewords of strictly smaller span lengths and a atomic codeword having the same conventional span and strictly smaller order of the first or the last nonzero component, one of which, b say, would start in the same position and have the same order of the first nonzero component as c . Therefore b have the same starting position and order of the first nonzero component as a , which contradict the above Theorem 3.1. ■

Therefore, we have the following.

Corollary 3.2: Any set of k codewords of a linear code C of length n and p -dimension k over Z_{p^α} in row echelon form with the same set of characteristic triples as a biproper p -basis of C is also a biproper p -basis for C in row echelon form.

Theorem 3.5: Let C be a linear code of length n and p -dimension k over Z_{p^α} . Then the p -dimension of any subcode S of C in which every codeword c has a conventional span contained in $(a, b]$ and the maximal orders of the a -th and

the b -th components of codewords are respectively s and t , is equal to the number of atomic classes in C whose conventional span is in $(a, b]$ and order of the a -th component is not higher than s and order of the b -th component is not higher than t .

Proof: Every codeword c in S can be expressed as a p -linear combination of atomic codewords from different atomic classes. Then in the p -linear combination, no atomic codeword with conventional span not in $(a, b]$ or whose conventional span is in $(a, b]$ and order of the a -th component is higher than s or order of the b -th component is higher than t can be used. Therefore, we finish the proof. ■

Theorem 3.6: Let C be a linear code of length n and p -dimension k over Z_{p^α} . Then the set of codeword characteristic triples achieved by C is completely determined by the set of characteristic triples of atomic classes in the code.

Proof: Every codeword c in C can be expressed as a p -linear combination $\sum_j a_j x_j$ where $a_j \in Z_p$, $a_j \neq 0$ and x_j are atomic with characteristic triple $((\angle(x_j), \triangleright(x_j)), o_1(x_j), o_2(x_j))$. Then the characteristic triple of c is

$$((\min_j \{\angle(x_j)\}, \max_j \{\triangleright(x_j)\}), \max_{\substack{\angle(x_m) = \\ \min_j \{\angle(x_j)\}}} \{o_1(x_m)\}, \max_{\substack{\triangleright(x_t) = \\ \max_j \{\triangleright(x_j)\}}} \{o_2(x_t)\}),$$

and hence is determined by the set of characteristic triples of atomic classes. ■

Theorem 3.7: Let C be a linear code of length n and p -dimension k over Z_{p^α} . Then any equivalence class of minimum nonzero span length is atomic and consists of multiples of a single codeword by units in Z_{p^α} .

Proof: If an element of the equivalence class of minimum nonzero span length is not atomic, it can be expressed as a p -linear combination of codewords of strictly smaller span lengths or a p -linear combination of a codeword having strictly smaller span length and a codeword having the same conventional span and strictly smaller order of the first or the last nonzero component, which is a contradiction. Suppose two codewords c_1 and c_2 belong to the same equivalence class of minimum nonzero span length. Then all multiples of c_1 and c_2 by units in Z_{p^α} also belong to the same atomic class. There exists a unit α in Z_{p^α} such that $c_1 - \alpha c_2$ starts later than c_1 . If $c_1 - \alpha c_2 \neq 0$, then $c_1 - \alpha c_2$ is a codeword of smaller span length than c_1 . Therefore $c_1 - \alpha c_2 = 0$, which implies $c_1 = \alpha c_2$. ■

IV. CONSTRUCTION OF MINIMAL TAIL-BITING TRELLISES

In this section, we prove the conjecture in [12] is true that every minimal tail-biting trellis for a group code over a finite abelian group can be constructed from its characteristic generators, which extends the work of Koetter and Vardy who treated the case of a linear code over a field. Since for arbitrary finite abelian group, it is sufficient to consider the case of a linear code over a ring Z_{p^α} . Thus we first focus on our discussion on linear codes over Z_{p^α} .

Theorem 4.1: Let $X = \{x_1, x_2, \dots, x_k\}$ be a p -basis for a linear code C over Z_{p^α} and $Y = \{y_1, y_2, \dots, y_k\}$ be a biproper p -basis for C in row echelon form. Let $T = T_{x_1} \times \dots \times T_{x_k}$ is a $\prec_\Theta$ minimal linear tail-biting trellis for C . Then for each $1 \leq i \leq k$, either $0 \in [x_i]$ or there exists $y \in Y$ such that x_i belongs to the same equivalence class of C , namely, $([x_i], o_1(x_i), o_2(x_i)) = ((\prec(y), \triangleright(y)), o_1(y), o_2(y))$.

Proof: We proceed by induction on p -dimension k of C . If $k = 1$ the result is clear by Theorem 3.3. Suppose that $k > 1$. It is easy to show that $\{x_2, \dots, x_k\}$ is a p -linearly independent p -generator sequence. Let $C' = p\text{-span}(\{x_2, \dots, x_k\})$ be a subcode of C . It is obvious that $T' = T_{x_2} \times \dots \times T_{x_k}$ is a $\prec_\Theta$ minimal linear tail-biting trellis for C' . By definition the p -dimension of C' is $k - 1$ and $\{x_2, \dots, x_k\}$ is a p -basis for C' . Therefore, every codeword in C' can be expressed as a linear combination of atomic codewords from $k - 1$ distinct atomic classes of C by Theorem 3.5. Let $Z' = \{z_2, \dots, z_k\}$ be a complete set of representatives of the $k - 1$ distinct atomic classes in row echelon form. By Theorem 3.3, $Z' = \{z_2, \dots, z_k\}$ is a biproper p -basis for C' in row echelon form. Then by induction for each $2 \leq i \leq k$, either $0 \in [x_i]$ or there exists $z \in Z'$ such that x_i belongs to the same equivalence class of C , namely, $([x_i], o_1(x_i), o_2(x_i)) = ((\prec(z), \triangleright(z)), o_1(z), o_2(z))$.

Now, we take a representative z_1 of the remaining atomic class of C such that $Z = \{z_1, z_2, \dots, z_k\}$ a complete set of representatives of the k distinct atomic classes. We rearrange the order of elements in Z such that $Z = \{z_1, z_2, \dots, z_k\}$ is a complete set of atomic class representatives in row echelon form. By Theorem 3.3, $Z = \{z_1, z_2, \dots, z_k\}$ is a biproper p -basis for C in row echelon form.

Suppose that $0 \notin [x_1]$. Then $[x_1] = (\prec(x_1), \triangleright(x_1))$. Since Z is a biproper p -basis for C , the codeword x_1 can be expressed as a p -linear combination of the elements of Z , that is,

$$x_1 = \sum_{1 \leq j \leq k} a_j z_j \quad (12)$$

where $a_j \in Z_p$. Since $Z = \{z_1, z_2, \dots, z_k\}$ is a biproper p -basis for C in row echelon form, it follows that if a_{j_1} is the first nonzero coefficient in the expression of x_1 , then $\prec(x_1) = \prec(z_{j_1})$, $o_1(x_1) = o_1(z_{j_1})$ and $\triangleright(x_1) \geq \triangleright(z_{j_1})$.

(1) $\triangleright(x_1) = \triangleright(z_{j_1})$. In this case, if $o_2(x_i) = o_2(y_{j_1})$, we are done. Otherwise, $o_2(x_1) > o_2(z_{j_1})$. Then there exists j_2 , $a_{j_2} \neq 0$ in (12), $j_1 < j_2 \leq k$, such that $\triangleright(x_1) = \triangleright(z_{j_2})$, $o_2(x_1) = o_2(z_{j_2})$ and $\prec(x_1) \leq \prec(z_{j_2})$. Suppose that $\prec(x_1) = \prec(z_{j_2})$ and $o_1(x_1) > o_1(z_{j_2})$. Since that $\prec(x_1) = \prec(z_{j_1})$ and $o_1(x_1) = o_1(z_{j_1})$, it follows that there exists a unit a in Z_{p^α} such that $s = az_{j_1} - x_1$ ends earlier than x_1 . Then s can be expressed as the p -linear combination that uses codewords of $Y = \{y_1, y_2, \dots, y_k\}$ later than z_{j_2} and $az_{j_1} = x_1 + s$ can be expressed as the p -linear combination that uses z_{j_1} , z_{j_2} and codewords of $Y = \{y_1, y_2, \dots, y_k\}$ later than z_{j_2} . Then $\prec(az_{j_1}) = \prec(z_{j_2})$ and $o_2(az_{j_1}) \geq o_2(z_{j_2})$, which is a contradiction. Therefore, $\prec(x_1) < \prec(z_{j_2})$. Since $X = \{x_1, x_2, \dots, x_k\}$ is a p -basis for a linear code C over Z_{p^α} , it follows that $z_{j_2} \in C$ can be expressed as the p -linear combination

$$z_{j_2} = c_1 x_1 + c_2 x_2 + \dots + c_k x_k$$

for some $c_1, c_2, \dots, c_k \in Z_p$. If $c_1 \neq 0$, then $\{z_{j_2}, x_2, \dots, x_k\}$ is a p -basis for C , and, therefore, the trellis $T' = T_{z_{j_2}} \times T_{x_2} \times \dots \times T_{x_k}$ represents C . But since $\triangleright(x_1) = \triangleright(z_{j_2})$, $o_2(x_1) = o_2(z_{j_2})$ and $\prec(x_1) < \prec(z_{j_2})$, it follows that $[z_{j_2}] \subset [x_1]$, and, therefore, $T_{z_{j_2}} \prec_\Theta T_{x_1}$. Therefore, $T' \prec_\Theta T$, and T is not $\prec_\Theta$ minimal. Hence, $c_1 = 0$. Since $\triangleright(x_1) = \triangleright(z_{j_2})$ and $o_2(x_1) = o_2(z_{j_2})$, it follows that there exists a unit c in Z_{p^α} such that $t = z_{j_2} + cx_1 = c_2 x_2 + \dots + c_k x_k + cx_1$ ends earlier than z_{j_2} . By Lemma 6.1 [20], t can be expressed as the p -linear combination of x_1 and later codewords of $X = \{x_1, x_2, \dots, x_k\}$. Hence we have a p -basis $\{t, x_2, \dots, x_k\}$ for C , and, therefore, the trellis $T'' = T_t \times T_{x_2} \times \dots \times T_{x_k}$ represents C . But since $\prec(t) = \prec(x_1)$, and $\triangleright(t) < \triangleright(x_1)$, it follows that $[t] \subset [x_1]$ and $T_t \prec_\Theta T_{x_1}$. Therefore, $T'' \prec_\Theta T$, and T is not $\prec_\Theta$ minimal. Thus, it leads to a contradiction.

(2) $\triangleright(x_1) > \triangleright(z_{j_1})$. Since $X = \{x_1, x_2, \dots, x_k\}$ is a p -basis for a linear code C over Z_{p^α} , it follows that $z_{j_1} \in C$ can be expressed as the p -linear combination

$$z_{j_1} = b_1 x_1 + b_2 x_2 + \dots + b_k x_k$$

for some $b_1, b_2, \dots, b_k \in Z_p$. If $b_1 \neq 0$, then $\{z_{j_1}, x_2, \dots, x_k\}$ is a p -basis for C , and, therefore, the trellis $T' = T_{z_{j_1}} \times T_{x_2} \times \dots \times T_{x_k}$ represents C . But since $\prec(x_1) = \prec(z_{j_1})$, and $\triangleright(x_1) > \triangleright(z_{j_1})$, it follows that $[z_{j_1}] \subset [x_1]$ and $T_{z_{j_1}} \prec_\Theta T_{x_1}$. Therefore, $T' \prec_\Theta T$, and T is not $\prec_\Theta$ minimal. Hence, $b_1 = 0$. Since $\prec(x_1) = \prec(z_{j_1})$ and $o_1(x_1) = o_1(z_{j_1})$, there exists a unit b in Z_{p^α} such that $u = z_{j_1} + bx_1 = b_2 x_2 + \dots + b_k x_k + bx_1$ starts later than z_{j_1} . By Lemma 6.1 [20], u can be expressed as the p -linear combination of x_1 and later codewords of $X = \{x_1, x_2, \dots, x_k\}$. Hence we have a p -basis $\{u, x_2, \dots, x_k\}$ for C , and, therefore, the trellis $T'' = T_u \times T_{x_2} \times \dots \times T_{x_k}$ represents C . But since $\prec(u) \geq \prec(z_{j_1}) + 1 = \prec(x_1) + 1$, and $\triangleright(u) = \triangleright(x_1)$, it follows that $[u] \subset [x_1]$ and $T_u \prec_\Theta T_{x_1}$. Therefore, $T'' \prec_\Theta T$, and T is not $\prec_\Theta$ minimal. Thus, it leads to a contradiction.

Therefore, $([x_1], o_1(x_1), o_2(x_1)) = ((\prec(z_{j_1}), \triangleright(z_{j_1})), o_1(z_{j_1}), o_2(z_{j_1}))$. Hence, for each $1 \leq i \leq k$, either $0 \in [x_i]$ or there exists $z \in Z$ such that x_i belongs to the same equivalence class of C . Since z is atomic, it follows that there exists $y \in Y$ such that z belongs to the same equivalence class of C . Thus, for each $1 \leq i \leq k$, either $0 \in [x_i]$ or there exists $y \in Y$ such that x_i belongs to the same equivalence class of C . ■

Next, we generalize the result of Theorem 4.1. We let $\sigma_j(\cdot)$ denote a cyclic shift to the left j times, and consider the corresponding cyclic shift of C , namely, $C_j = \sigma_j(C)$. Let $\rho_j(\cdot)$ denote a cyclic shift to the right j times. For $x = (x_0, x_1, \dots, x_k) \in Z_{p^\alpha}$, $\rho_j(x) = (x_{n-j}, \dots, x_{n-1}, x_0, x_1, \dots, x_{n-1-j})$. Let $[x] = (a, b]$, a span of x , define the action of ρ_j on a quadruple as follows:

$$\begin{aligned} \rho_j((x, [x], o(x_a), o(x_b))) &= (\rho_j(x), (a+j, b+j], \\ & o(\rho_j(x)_{a+j}), o(\rho_j(x)_{b+j})), \end{aligned} \quad (13)$$

where $o(\rho_j(x)_{a+j})$ is the order of the $(a+j)$ -th component of $\rho_j(x)$ in Z_{p^α} . Clearly, $x_a = \rho_j(x)_{a+j}$, $x_b = \rho_j(x)_{b+j}$ and $\rho_j((x, [x], o(x_a), o(x_b))) = (\rho_j(x), (a+j, b+j], o(x_a), o(x_b))$.

Theorem 4.2: Let $X = \{x_1, x_2, \dots, x_k\}$ be a p -basis for a linear code C of length n and p -dimension k over Z_{p^α} . Let j be any integer in the set $\mathcal{I} = \{0, 1, \dots, n-1\}$. Let $Y_j = \{y_1, y_2, \dots, y_k\}$ be a biproper p -basis for $C_j = \sigma_j(C)$ in row echelon form. Let $T = T_{x_1} \times \dots \times T_{x_k}$ is a $\prec_\Theta$ minimal linear tail-biting trellis for C . Then for each $1 \leq i \leq k$, either $j \in [x_i]$ or there exists $y \in Y_j$ such that $\sigma_j(x_i)$ belong to the same equivalence class of C_j , namely, $([x_i], o(x_a), o(x_b)) = ((\triangleleft(y) + j, \triangleright(y) + j], o_1(y), o_2(y))$, where $[x_i] = (a, b]$.

Proof: This follows immediately by combining Theorem 4.1 and Proposition 3.2 in [12]. ■

Now, we can generalize the definition of characteristic generators for a linear code over a field to a linear code C over Z_{p^α} . Theorem 4.2 makes it possible to characterize all the $\prec_\Theta$ minimal linear tail-biting trellises for a linear code C over Z_{p^α} in terms of a small set of characteristic generators. For each $j \in \mathcal{I}$, let Y_j denote the lexicographically first biproper p -basis for $C_j = \sigma_j(C)$ in row echelon form, define $X_j = \rho_j(Y_j)$. Then X_j is a subset of C for all j .

Definition 4.1: Let C be a linear code of length n over Z_{p^α} . A *characteristic generator* for C is a quadruple consisting of a codeword $x = (x_0, x_1, \dots, x_{n-1}) \in C$, a interval $[x] = (a, b]$ such that x_a, x_b are nonzero, $o(x_a)$ and $o(x_b)$. We also let $Y_j = \{(y, (c, d], o(y_c), o(y_d)) \mid y \in Y_j, (c, d] \text{ is the conventional span of } y\}$. The set of all the characteristic generators for C is given by

$$X = X_0 \cup X_1 \cup \dots \cup X_{n-1} \\ = Y_0 \cup \rho_1(Y_1) \cup \dots \cup \rho_{n-1}(Y_{n-1}) \quad (14)$$

with the understanding that $[x] = (\triangleleft(y) + j, \triangleright(y) + j]$, $o(x_a) = o_1(y)$ and $o(x_b) = o_2(y)$ for each $x \in X_j$, where $y = \sigma_j(x)$, $[x] = (a, b]$. The *characteristic matrix* $\mathcal{X}$ for C is the $|X| \times n$ matrix having the elements of X as its rows.

Theorem 4.3: Let $X = \{x_1, x_2, \dots, x_k\}$ be a p -basis for a linear code C of length n and p -dimension k over Z_{p^α} . If $T = T_{x_1} \times T_{x_2} \times \dots \times T_{x_k}$ is a $\prec_\Theta$ minimal linear tail-biting trellis for C , then the trellis T can be constructed as

$$T = T_{z_1} \times T_{z_2} \times \dots \times T_{z_k}$$

where $z_1, z_2, \dots, z_k$ are k p -linearly independent characteristic generators for C .

Proof: It is obvious that $[x_i] \neq \mathcal{I}$ for all $i = 1, 2, \dots, k$. Otherwise, we can replace T_{x_i} by a strictly smaller trellis T'_{x_i} for x_i using the span $[x_i] = (0, n-1]$. Hence, there exists at least one $j \in \mathcal{I}$ such that $j \notin [x_i]$.

We proceed by induction on p -dimension k of C . If $k = 1$, there exists $y \in Y_j$ such that $\sigma_j(x_1)$ belong to the same equivalence class of C_j , namely, $([x_1], o(x_a), o(x_b)) = ((\triangleleft(y) + j, \triangleright(y) + j], o_1(y), o_2(y))$, where $[x_1] = (a, b]$. In the case, $\rho_j(y)$ is a p -basis, and, therefore, the trellis $T' = T_{\rho_j(y)}$ represents C . Then $T = T' = T_{\rho_j(y)}$. The result is proved. Suppose that $k > 1$. It is easy to show that $\{x_2, \dots, x_k\}$ is a p -linearly independent p -generator sequence. Let $C' = p\text{-span}(\{x_2, \dots, x_k\})$ be a subcode of C . It is obvious that $T' = T_{x_2} \times \dots \times T_{x_k}$ is a $\prec_\Theta$ minimal linear tail-biting trellis

for C' . By definition the p -dimension of C' is $k-1$. Then by induction the trellis T' can be constructed as

$$T' = T_{z_2} \times \dots \times T_{z_k}$$

where $z_2, \dots, z_k$ are $k-1$ p -linearly independent characteristic generators for C' . It is easy to show that $z_2, \dots, z_k$ are also $k-1$ p -linearly independent characteristic generators and $x_1, z_2, \dots, z_k$ is also a p -basis for C .

Now, there exists at least one $j \in \mathcal{I}$ such that $j \notin [x_1]$. This implies that there exists $y \in Y_j$ such that $\sigma_j(x_1)$ belong to the same equivalence class of C_j , namely, $([x_1], o(x_a), o(x_b)) = ((\triangleleft(y) + j, \triangleright(y) + j], o_1(y), o_2(y))$, where $[x_1] = (a, b]$. Since $x_1, z_2, \dots, z_k$ is a p -basis for C , it follows that $\rho_j(y)$ can be expressed as a p -linear combination

$$\rho_j(y) = a_1 x_1 + a_2 z_2 + \dots + a_k z_k,$$

where $a_j \in Z_p$. If $a_1 = 0$, then there exists a unit u in Z_{p^α} such that the span of $t = \rho_j(y) + u x_1 = a_2 z_2 + \dots + a_k z_k + u x_1$ starts later than x_1 . By Lemma 6.1 [20], t can be expressed as the p -linear combination of x_1 and later codewords of $\{x_1, z_2, \dots, z_k\}$. Hence we have a p -basis $\{t, z_2, \dots, z_k\}$ for C , and, therefore, the trellis $T' = T_t \times T_{z_2} \times \dots \times T_{z_k}$ represents C . But since $([x_1], o(x_a), o(x_b)) = ((\triangleleft(y) + j, \triangleright(y) + j], o_1(y), o_2(y))$, where $[x_1] = (a, b]$, it follows that $[t] \subset [x_1]$ and $T_t \prec_\Theta T_{x_1}$. Therefore, $T' \prec_\Theta T$, and T is not $\prec_\Theta$ minimal. Thus, it leads to a contradiction. Hence, $a_1 \neq 0$ and we have a p -basis $\{\rho_j(y), z_2, \dots, z_k\}$ for C , and, therefore, the trellis $T'' = T_{\rho_j(y)} \times T_{z_2} \times \dots \times T_{z_k}$ represents C . Then $T = T'' = T_{\rho_j(y)} \times T_{z_2} \times \dots \times T_{z_k}$, where $\{\rho_j(y), z_2, \dots, z_k\}$ are k p -linearly independent characteristic generators for C . ■

We review a key theorem in [13] as follows:

Lemma 4.1: Let T be a group tail-biting trellis over an abelian group. Then T can be factored as $T = T_{x_1} \times T_{x_2} \times \dots \times T_{x_k}$, where T_{x_i} is elementary trellis over a group, for $i = 1, 2, \dots, k$.

Now, we have the following.

Theorem 4.4: Let T be a linear tail-biting trellis over Z_{p^α} . Then T can be factored as $T = T_{x_1} \times T_{p x_1} \times \dots \times T_{p^{\alpha_1} x_1} \times T_{x_2} \times T_{p x_2} \times \dots \times T_{p^{\alpha_2} x_2} \times \dots \times T_{x_k} \times T_{p x_k} \times \dots \times T_{p^{\alpha_k} x_k}$, where $T_{x_i}, T_{p x_i}, \dots, T_{p^{\alpha_i} x_i}$ are elementary trellises over Z_{p^α} , and the order of x_i is p^{α_i} , for $i = 1, 2, \dots, k$.

Proof: Obviously, T is also a group tail-biting trellis over the additive group of Z_{p^α} . By Lemma 4.1, as a group tail-biting trellis, T can be factored as $T = T_{x_1} \times T_{x_2} \times \dots \times T_{x_k}$, where $T_{x_1}, T_{x_2}, \dots, T_{x_k}$ are elementary trellises over a group. For $i = 1, 2, \dots, k$, the elementary tail-biting trellis T_{x_i} is a minimal group tail-biting trellis for group code $\langle x_i \rangle$ over the additive group of Z_{p^α} , then T_{x_i} is also a minimal linear tail-biting trellis for linear code $\langle x_i \rangle$ over Z_{p^α} . Let the order of x_i is p^{α_i} . Since the linear code $\langle x_i \rangle$ have a p -basis $x_i, p x_i, \dots, p^{\alpha_i} x_i$, $T_{x_i} = T_{x_i} \times T_{p x_i} \times \dots \times T_{p^{\alpha_i} x_i}$. ■

Theorem 4.5: Every linear tail-biting trellis T for a linear code C of length n and p -dimension k over Z_{p^α} that is

minimal under $\prec_\Theta$ can be constructed as

$$T = T_{z_1} \times T_{z_2} \times \cdots \times T_{z_k}$$

where $z_1, z_2, \dots, z_k$ are k p -linearly independent characteristic generators for C .

Proof: By Theorem 4.4, the trellis T can be factored as $T = T_{x_1} \times T_{px_1} \times \cdots \times T_{p^{\alpha_1}x_1} \times T_{x_2} \times T_{px_2} \times \cdots \times T_{p^{\alpha_2}x_2} \times \cdots \times T_{x_m} \times T_{px_m} \times \cdots \times T_{p^{\alpha_m}x_m}$, where $T_{x_i}, T_{px_i}, \dots, T_{p^{\alpha_i}x_i}$ are elementary trellises over Z_{p^α} , and the order of x_i is p^{α_i} , for $i = 1, 2, \dots, m$. If $\alpha_1 + \alpha_2 + \cdots + \alpha_m > k$, then $x_1, px_1, \dots, p^{\alpha_1}x_1, x_2, px_2, \dots, p^{\alpha_2}x_2, \dots, x_m, px_m, \dots, p^{\alpha_m}x_m$ are p -linearly dependent. Suppose that $p^j x_i$ can be expressed as a p -linear combination of $p^{j+1}x_i, \dots, x_m, px_m, \dots, p^{\alpha_m}x_m$, where $j \neq \alpha_m$ or $i \neq m$. Therefore, $T' = T_{x_1} \times T_{px_1} \times \cdots \times T_{p^{\alpha_1}x_1} \times T_{x_2} \times T_{px_2} \times \cdots \times T_{p^{\alpha_2}x_2} \times \cdots \times T_{p^{j-1}x_i} \times T_{p^{j+1}x_i} \times \cdots \times T_{x_m} \times T_{px_m} \times \cdots \times T_{p^{\alpha_m}x_m}$ is a linear trellis such that $C(T) = C(T')$ and $T' \prec_\Theta T$. Hence $\alpha_1 + \alpha_2 + \cdots + \alpha_m \leq k$ and $x_1, px_1, \dots, p^{\alpha_1}x_1, x_2, px_2, \dots, p^{\alpha_2}x_2, \dots, x_m, px_m, \dots, p^{\alpha_m}x_m$ are p -linearly independent. Clearly, $C(T) = C$ if and only if $C = p\text{-span}(\{x_1, px_1, \dots, p^{\alpha_1}x_1, x_2, px_2, \dots, p^{\alpha_2}x_2, \dots, x_m, px_m, \dots, p^{\alpha_m}x_m\})$, which implies $\alpha_1 + \alpha_2 + \cdots + \alpha_m = k$ and $\{x_1, px_1, \dots, p^{\alpha_1}x_1, x_2, px_2, \dots, p^{\alpha_2}x_2, \dots, x_m, px_m, \dots, p^{\alpha_m}x_m\}$ is a p -basis for C . By Theorem 4.3, the trellis T can be constructed as

$$T = T_{z_1} \times T_{z_2} \times \cdots \times T_{z_k}$$

where $z_1, z_2, \dots, z_k$ are k p -linearly independent characteristic generators for C . ■

A similar argument makes it possible to characterize minimal linear tail-biting trellises under any of the minimality orders defined in (4)-(9) for a linear code C over Z_{p^α} .

Theorem 4.6: Every linear tail-biting trellis T for a linear code C of length n and p -dimension k over Z_{p^α} that is minimal under any of the minimality orders defined in (4)-(9) can be constructed as

$$T = T_{z_1} \times T_{z_2} \times \cdots \times T_{z_k}$$

where $z_1, z_2, \dots, z_k$ are k p -linearly independent characteristic generators for C .

Proof: It is obvious that the set of minimal trellises with respect to these three orders, the vertex-product order $\prec_\Pi$, the vertex-max order $\prec_{\max}$, and the vertex-sum order $\prec_\Sigma$, is a subset of the set of $\prec_\Theta$ -minimal trellises, and the result follows directly from Theorem 4.5. Similarly, with respect to the other three orders $\prec_{\Pi\mathcal{E}}$, $\prec_{\max\mathcal{E}}$ and $\prec_{\Sigma\mathcal{E}}$ introduced in (7)-(9), the set of minimal trellises is a subset of the set of minimal trellises under the order $\prec_\mathcal{E}$ defined by the edge-class profile $(|E_0|, |E_1|, \dots, |E_{n-1}|)$ of the trellis. Observe that the proof of Theorem 4.1 (and, hence, also of Theorem 4.2, Theorem 4.3 and Theorem 4.5) holds without change if we replace " $\prec_\Theta$ " with " $\prec_\mathcal{E}$ " throughout. Thus, Theorem 4.5 holds for $\prec_\mathcal{E}$ -minimal trellises as well, and the claim with respect to the $\prec_{\Pi\mathcal{E}}$, $\prec_{\max\mathcal{E}}$ and $\prec_{\Sigma\mathcal{E}}$ orders follows. ■

Now we go back to the codes over finite abelian groups. Let G be a finite abelian group and C be a group code of length

n over G . Then G can be decomposed into a direct product of cyclic groups, i. e.,

$$G = (Q_{p_1^{\alpha_{11}}} + \cdots + Q_{p_1^{\alpha_{1m_1}}}) + \cdots + (Q_{p_r^{\alpha_{r1}}} + \cdots + Q_{p_r^{\alpha_{rm_r}}}),$$

where $p_1, \dots, p_r$ are distinct primes. We can decompose C into r codes $C_1, \dots, C_r$, i.e., $C = C_1 + \cdots + C_r$. Hence, it is sufficient to consider the case of a code over a p -group H , i.e., $H = Q_{p^{\alpha_1}} + \cdots + Q_{p^{\alpha_m}}$, where $\alpha_1 \leq \cdots \leq \alpha_m$. Then by Lemma 8.5 in [20] a code of length n over p -group H is equivalent to a linear code of length mn over $Z_{p^{\alpha_m}}$. If we denote the minimal trellis for a code C over a finite abelian group G by T , the minimal trellis for the code C_i over p_i -group H_i by T_i , then $T = T_1 \times \cdots \times T_r$. It is easy to see that T_i is a trellis that can be obtained by sectionalizing a minimal trellis for linear code S_i of length $m_i n$ over $Z_{p_i^{\alpha_{im_i}}}$, where the code S_i is equivalent to the code C_i over p_i -group H_i .

We can obtain a generator matrix A_i for C_i over p_i -group H_i from a generator matrix A for C , where the element in matrix A_i in the j -th row and the l -th column is a_{jl}^i if a_{jl} in matrix A in the j -th row and the l -th column can be decomposed into a direct product of $a_{jl}^1, a_{jl}^2, \dots, a_{jl}^r$, $a_{jl}^i \in H_i$ for $i = 1, 2, \dots, r$. We also can obtain a generator matrix B_i for the linear code S_i of length $m_i n$ over $Z_{p_i^{\alpha_{im_i}}}$ from A_i by Lemma 8.6 in [20]. By Theorem 4.5, we can construct a minimal tail-biting trellis T'_i for S_i , for $i = 1, 2, \dots, r$. Then sectionalizing this trellis will give a minimal tail-biting trellis T_i for the code C_i over p_i -group H_i . Thus, the product trellis $T = T_1 \times \cdots \times T_r$ is a minimal tail-biting trellis for C over a finite abelian group G . Therefore, we show that although minimal tail-biting trellises for group codes are generally not unique, every minimal linear tail-biting trellis for a group code over a finite abelian group necessarily can be constructed from its characteristic matrix.

V. COMPUTATION OF THE CHARACTERISTIC MATRIX

Let C be a linear code of length n and p -dimension k over Z_{p^α} . The basic properties of characteristic generators for C are investigated in [30]. It was proved that the spans of any two characteristic generators for C do not start at the same position and have the same order of their starting components simultaneously and end at the same position and have the same order of their ending components simultaneously as well. The authors also proved that the number of characteristic generators for C is $\sum_{i \in \chi(C)} k_i$ and less than nk , where p^{k_i} , $0 \leq k_i \leq \alpha$, is the maximal order of the i -th components of codewords in C .

It follows from [30] that the characteristic matrix $\mathcal{X}$ for C is a $\sum_{i \in \chi(C)} k_i \times n$ matrix. For simplicity, we henceforth assume that $|\chi(C)| = n$ (otherwise, we puncture out the all-zero columns of C). Then the characteristic matrix $\mathcal{X}$ is a $\sum_{i=0}^{n-1} k_i \times n$ matrix, and $0 < k_i \leq \alpha$ for all $i = 0, 1, \dots, n-1$.

We now show how the characteristic matrix $\mathcal{X}$ can be computed from an arbitrary given p -generator sequence $V = \{v_1, v_2, \dots, v_k\}$ for the module C over Z_{p^α} . The first step is to convert this p -generator sequence into a biproper

p -basis in row echelon form. As is well known [20], this can be easily accomplished by Gaussian elimination, as follows:

Algorithm A

- 1) $S \leftarrow V$.
- 2) While there is a nonzero element in S do:
- 3) Find $S' \subseteq S$, the set of elements of S having the earliest starting position.
- 4) Find $S'' \subseteq S'$, the set of elements of S' having the highest order starting component.
- 5) pick the last element $v \in S''$, output it, and set $S \leftarrow S - \{v\}$.
- 6) For each remaining $u \in S''$, replace u in S by $u + av$, where $a \in Z_{p^\alpha}$ is such that $u + av$ starts later than u .
- 7) end.

The algorithm A given above starts with an arbitrary p -generator sequence $V = \{v_1, v_2, \dots, v_k\}$ for the module C over Z_{p^α} and finds a proper p -generator sequence in row echelon form, by Lemma 6.10 in [20] the proper p -generator sequence in row echelon form is a p -basis. Its running time is bounded by $O(n^3)$ operations over Z_{p^α} .

Algorithm B

- 1) $S \leftarrow W$.
- 2) While S is not biproper do:
- 3) Find $S' \subseteq S$, with $|S'| > 1$, elements having the latest ending position, and moreover such that their ending components are associate;
- 4) Let w be the last element in S' ;
- 5) For each remaining $u \in S'$, replace u in S by $u + aw$, where $a \in Z_{p^\alpha}$ is such that $u + aw$ ends earlier than u .
- 6) end.

The algorithm B given above starts with a proper p -generator sequence $W = \{w_1, w_2, \dots, w_k\}$ in row echelon form for the module C over Z_{p^α} and finds a biproper p -generator sequence in row echelon form. Its running time is bounded by $O(n^3)$ operations over Z_{p^α} . To ensure that the resulting biproper p -basis is the lexicographically first biproper p -basis for C in row echelon form, we need to select the lexicographically first codeword in each atomic equivalence class, this can be easily done as follows:

Algorithm C

- for all $i \in \{1, 2, \dots, k\}$ do
 while $(\exists x_j \text{ and } a \in Z_{p^\alpha} \text{ such that } [x_j] \subset [x_i]$
 and $x_i + ax_j \prec_L x_i)$
 do $x_i := x_i + ax_j$.

The complexity of Algorithm C is also at most $O(n^3)$. This immediately yields an $O(n^4)$ algorithm for the computation of the characteristic matrix. For each of the n cyclic shifts of C , compute the lexicographically first biproper p -basis in row echelon form using Algorithm A, Algorithm B and Algorithm

C, then rotate cyclically to the right and form the set of characteristic generators X as in (14).

However, we can simplify the computation of the characteristic matrix. since C has p^k elements and C is a subgroup of $Z_{p^\alpha}^n$ under the componentwise addition operation of Z_{p^α} , $k_i \leq k$ for all $i = 0, 1, \dots, n-1$, and therefore, for each $j \in \mathcal{I}$, the sets $\rho_j(Y_j)$ and $\rho_{j+1}(Y_{j+1})$ in (14) have at least $k - k_j$ characteristic generators in common by Corollary 9 in [30]. Then we obtain an efficient algorithm for computing the characteristic matrix as follows:

Algorithm I

Input: An arbitrary given p -generator sequence for a linear code C length $n = |\chi(C)|$ and p -dimension k over Z_{p^α} .

Output: The set X of n characteristic generators for C .

1) Using Algorithm A, Algorithm B and Algorithm C, compute $X_0 = \{x_1, x_2, \dots, x_k\}$, the lexicographically first biproper p -basis in row echelon form. Set $j := 0$. Also set $X = \{(x_1, [x_1], o_1(x_1), o_2(x_1)), (x_2, [x_2], o_1(x_2), o_2(x_2)), \dots, (x_k, [x_k], o_1(x_k), o_2(x_k))\}$, where $[x_i] = (\triangleleft(x_i), \triangleright(x_i))$ for all i .

2) Find the set $T \subseteq \{1, 2, \dots, k\}$ and $|T| = k_j$, such that $\triangleleft(x_t) = 0$ for each $t \in T$. Then do $x_i = \sigma_1(x_i)$ for all $i = 1, 2, \dots, k$.

3) For all $t \in T$ do, while $\exists i \in \{1, 2, \dots, k\} \setminus \{t\}$ and $o_2(x_i) < o_2(x_t)$ if $i \in T$ such that $\triangleleft(x_i) = \triangleleft(x_t)$ and $o_1(x_i) = o_1(x_t)$, do $x_t := x_t + ax_i$, where $a \in Z_{p^\alpha}$ is such that $x_t + ax_i$ starts later than x_t (and go back).

4) For all $t \in T$ do, while $\exists i \in \{1, 2, \dots, k\} \setminus \{t\}$, $o_2(x_i) < o_2(x_t)$ if $i \in T$ and $a \in Z_{p^\alpha}$ such that $(\triangleleft(x_i), \triangleright(x_i))$ is a proper subset of $(\triangleleft(x_t), \triangleright(x_t))$ and $x_t + ax_i \prec_L x_t$, do $x_t := x_t + ax_i$ (and go back).

5) Permuting all the elements in $\{x_1, x_2, \dots, x_k\}$ such that they are in row echelon form.

6) Set $j := j + 1$. If $(\rho_j(x_t), (\triangleleft(x_t) + j, \triangleright(x_t) + j), o_1(x_t), o_2(x_t))$ is not in x , add this pair to X . If $|X| = \sum_{i=0}^{n-1} k_i$, return X and exit; else go to the step 2).

The complexity of Algorithm I is at most $O(n^3)$.

We now show that above Algorithm I is reasonable. First, we prove that for $j = 0, 1, \dots, n-1$, if the set $\{x_1, x_2, \dots, x_k\}$ is the lexicographically first biproper p -basis in row echelon form of $C_j = \sigma_j(C)$, then, after the execution of the steps 2)-5), the set $\{x_1, x_2, \dots, x_k\}$ is the lexicographically first biproper p -basis in row echelon form of $C_{j+1} = \sigma_{j+1}(C)$. Then, by Theorem 8, Theorem 9 in [30] and the definition of biproper p -basis, the fact that $|\chi(C)| = n$ guarantees that there are $t_1, t_2, \dots, t_{k_j} \in \{1, 2, \dots, k\}$ such that $\triangleleft(x_{t_i}) = 0$, $o_1(x_{t_i}) = p^i$, $i = 1, 2, \dots, k_j$. Set $\{t_1, t_2, \dots, t_{k_j}\} = T$ and $|T| = k_j$. After the cyclic shift, the set $\{x_1, x_2, \dots, x_k\}$ is a p -basis of C_{j+1} . For all $i \in \{1, 2, \dots, k\} \setminus T$, the cyclic shift decreases $\triangleleft(x_i)$ and $\triangleright(x_i)$ by one. Thus all the elements in $\{x_1, x_2, \dots, x_k\} \setminus \{x_t | t \in T\}$ either start at different positions or start the same position but their starting components have different orders and either end at different positions or end the same position but their ending components have different orders. Moreover, the elements of $\{x_t | t \in T\}$

are all elements in $\{x_1, x_2, \dots, x_k\}$ with the property that $\triangleright(x_t) = n - 1$ and the orders of their ending components are $p^1, p^2, \dots, p^{k_j}$. This property obviously remains after the execution of the step 3). And this step makes sure that $(\triangleleft(x_i), o_1(x_i)) \neq (\triangleleft(x_t), o_1(x_t))$ for all $t \in T$ and $i \in \{1, 2, \dots, k\} \setminus \{t\}$. Then the set $\{x_1, x_2, \dots, x_k\}$ is a biproper p -basis of C_{j+1} after the step 3). Each element in $\{x_1, x_2, \dots, x_k\} \setminus \{x_t | t \in T\}$ is lexicographically first in its atomic equivalence class since this property is preserved by the cyclic shift. After the step 4), each x_t for $t \in T$ is also lexicographically first in its atomic equivalence class. Therefore, $\{x_1, x_2, \dots, x_k\}$ is the lexicographically first biproper p -basis of C_{j+1} . After the step 5), $\{x_1, x_2, \dots, x_k\}$ is the lexicographically first biproper p -basis in row echelon form of C_{j+1} .

Next, we only need to prove that Algorithm I eventually terminates with $|X| = \sum_{i=0}^{n-1} k_i$. Since the elements of $\{x_t | t \in T\}$ are all elements in $\{x_1, x_2, \dots, x_k\}$ with the property that $\triangleright(x_t) = n - 1$ and the orders of their ending components are $p^1, p^2, \dots, p^{k_j}$, $\triangleright(x_t) + j = j - 1$ and the orders of ending components of the spans of the elements in $\{\rho_j(x_t) | t \in T\}$ are $p^1, p^2, \dots, p^{k_j}$, for $j = 0, 1, \dots, n - 1$. Then after at most n iterations, the set X contains characteristic generators with spans ending at every position in $\{0, 1, \dots, n - 1\}$ and the orders of ending components of the spans are $p^1, p^2, \dots, p^{k_j}$ at ending position j , for $j = 0, 1, \dots, n - 1$. Therefore, $|X| = \sum_{i=0}^{n-1} k_i$.

Remark 5.1: We can delete the step Algorithm C in 1), 4) and 5), for the notations of lexicographic order and proper p -basis in row echelon form were introduced for notational convenience only. In the step 6), add the pair $(\rho_j(x_t), (\triangleleft(x_t) + j, \triangleright(x_t) + j], o_1(x_t), o_2(x_t)))$ to X only if X does not contain any characteristic generator with $((\triangleleft(x_t) + j, \triangleright(x_t) + j], o_1(x_t), o_2(x_t)))$. This simplification eliminates a number of operations at each iteration, but the complexity of the Algorithm I remains at most $O(n^3)$.

Example 5.1: Consider the code over Z_8 generated by:

$$\begin{pmatrix} 1 & 2 & 1 & 2 \\ 2 & 0 & 4 & 2 \\ 0 & 0 & 4 & 4 \end{pmatrix}.$$

By Lemma 6.4, a p -generator sequence of the code is given below.

$$\begin{pmatrix} 1 & 2 & 1 & 2 \\ 2 & 4 & 2 & 4 \\ 4 & 0 & 4 & 0 \\ 2 & 0 & 4 & 2 \\ 4 & 0 & 0 & 4 \\ 0 & 0 & 4 & 4 \end{pmatrix}$$

Using Algorithm A, we get a proper p -basis in row echelon form as follows:

$$\begin{pmatrix} 1 & 2 & 1 & 2 \\ 2 & 4 & 2 & 4 \\ 4 & 0 & 4 & 0 \\ 0 & 4 & 2 & 6 \\ 0 & 0 & 4 & 4 \end{pmatrix}$$

Using Algorithm B and Algorithm C, we get the lexicographically first biproper p -basis in row echelon form of C . In the code, $\sum_{i=0}^3 k_i = 10$, then Algorithm I terminates in two iterations. After the steps 2)-5) in Algorithm I, we can get the lexicographically first biproper p -bases in row echelon form of C_1, C_2 . The lexicographically first biproper p -bases in row echelon form of C, C_1, C_2 are given by

$$Y_0 = \begin{pmatrix} 1 & 6 & 3 & 0 \\ 2 & 4 & 6 & 0 \\ 4 & 0 & 4 & 0 \\ 0 & 4 & 2 & 6 \\ 0 & 0 & 4 & 4 \end{pmatrix},$$

$$Y_1 = \begin{pmatrix} 2 & 1 & 2 & 1 \\ 4 & 2 & 6 & 0 \\ 0 & 4 & 4 & 0 \\ 0 & 0 & 2 & 6 \\ 0 & 0 & 4 & 4 \end{pmatrix}, \quad Y_2 = \begin{pmatrix} 1 & 2 & 1 & 2 \\ 2 & 0 & 6 & 4 \\ 4 & 4 & 0 & 0 \\ 0 & 2 & 6 & 0 \\ 0 & 4 & 4 & 0 \end{pmatrix}$$

respectively. We get the characteristic matrix for C as follows:

$$\mathcal{X} = \begin{pmatrix} x_1 \\ x_2 \\ x_3 \\ x_4 \\ x_5 \\ x_6 \\ x_7 \\ x_8 \\ x_9 \\ x_{10} \end{pmatrix} = \begin{pmatrix} 1 & 6 & 3 & 0 \\ 2 & 4 & 6 & 0 \\ 4 & 0 & 4 & 0 \\ 0 & 4 & 2 & 6 \\ 0 & 0 & 4 & 4 \\ 1 & 2 & 1 & 2 \\ 6 & 0 & 0 & 2 \\ 4 & 0 & 0 & 4 \\ 1 & 2 & 1 & 2 \\ 6 & 4 & 2 & 0 \end{pmatrix} \begin{pmatrix} ((0, 2], 3, 3) \\ ((0, 2], 2, 2) \\ ((0, 2], 1, 1) \\ ((1, 3], 1, 2) \\ ((2, 3], 1, 1) \\ ((1, 0], 2, 3) \\ ((3, 0], 2, 2) \\ ((3, 0], 1, 1) \\ ((2, 1], 3, 2) \\ ((2, 1], 2, 1) \end{pmatrix}$$

Consider the minimal conventional trellises for C, C_1, C_2, C_3 , we obtain 4 minimal tail-biting trellises for C after an obvious permutation. By the Theorem 4.5, the set X of characteristic generators is the smallest set of generators from which all the $\prec_\Theta$ -minimal tail-biting trellises for C can be constructed. However, not every choice of 5 characteristic generators in X produces a $\prec_\Theta$ -minimal tail-biting trellis for C under the product construction. It is necessary for producing a $\prec_\Theta$ -minimal tail-biting trellis under the product construction to satisfy the condition that 5 characteristic generators for C are p -linearly independent.

Now we go back to the codes over finite abelian groups. Since a code over a finite abelian group can be decomposed into a direct product of codes over those abelian p -groups which are all Sylow p -subgroup of the group and a code of length n over p -group is equivalent to a linear code of length mn over Z_{p^α} , by using sectionalization and Algorithm I, we get an efficient algorithm for constructing the minimal tail-biting trellis of a group code over a finite abelian group, given a generator matrix, see the section IV.

VI. CONCLUSION

In this paper, we give a general solution to the problem of constructing minimal linear tail-biting trellises for group codes over finite abelian groups. Thus an important application of our algorithms is to the construction of minimal trellises for lattices and some famous nonlinear binary codes, including Kerdock, Preparata, and Goethals codes.

A research direction worth investigating is using the special structure of minimal tail-biting trellises for group codes to obtain faster decoding algorithms.

ACKNOWLEDGMENT

The authors would like to thank...

REFERENCES

- [1] J. K. Wolf, "Efficient maximum likelihood decoding of linear block codes using a trellis," *IEEE Trans. Inf. Theory*, vol. IT-24, pp. 76-80, 1978.
- [2] S. Aji, G. Horn, R. J. McEliece, and M. Xu, "Iterative mini-sum decoding of tail-biting codes," in *Proc. IEEE Workshop on Information Theory*, Killarney, Ireland, June 1998, pp. 68-69.
- [3] G. D. Forney, Jr., F. R. Kschischang, B. Marcus, and S. Tuncel, "Iterative decoding of tail-biting trellises and connections with symbolic dynamics," in *Codes, Systems, and Graphical Models, IMA Volumes in Mathematics and Its Applications*, B. Marcus and J. Rosenthal, Eds. New York: Springer-Verlag, Mar. 2001.
- [4] R. Y. Shao, S. Lin, and M. P. C. Fossorier, "Decoding of codes based on their tail biting trellises," in *Pro. IEEE Int. Symp. Information Theory*, Sorrento, Italy, June 2000, p. 342.
- [5] S. Lin, T. Kasami, T. Fujiwaraw, and M. Fossorier, *Trellises and trellis-based decoding algorithms for linear block codes*, Boston, MA, USA: Kluwer, 1998.
- [6] G. D. Forney, "The Viterbi algorithm," *Proc. IEEE*, vol. 61, pp. 268-276, Mar. 1973.
- [7] Y. Shany, Y. Be'ery, "Tail-biting trellises of block codes: trellis complexity and Viterbi decoding complexity," *IEICE Trans. Fundamentals*, vol. E82-A, pp. 2043-2051, Oct. 1999.
- [8] A. B. Kiely, S. J. Dolinar, Jr., R. J. McEliece, L. L. Ekroot, and Wei Lin, "Trellis decoding complexity of linear block codes," *IEEE Trans. Inf. Theory*, Vol. 42, pp. 1687-1697, Nov. 1996.
- [9] I. Reuven and Y. Be'ery, "Tailbiting trellises of block codes: trellis complexity and Viterbi decoding complexity," *IEICE Trans. Fundamentals*, Vol. E82-A, pp. 2043-2051, Oct. 1999.
- [10] G. Viswanath and B. S. Rajan, "Minimal tail-biting trellises for linear MDS codes over F_{p^m} ," in *Pro. IEEE Int. Symp. Information Theory*, Sorrento, Italy, June 2000, p. 118.
- [11] P. Shankar, P. N. A. Kumar, H. Singh, and B. S. Rajan, *Minimal tail-biting trellises for certain cyclic block codes are easy to construct*, in *ICALP, F. Orejas, P. G. Spirakis, and J. Van Leeuwen*, Eds. Berlin: Springer-Verlag, 2001, pp. 627-638.
- [12] R. Koetter and A. Vardy, "The structure of tail-biting trellises: minimality and basic principals," *IEEE Trans. Inf. Theory*, vol. 49, pp. 2081-2105, Sep. 2003.
- [13] R. Koetter and A. Vardy, "On the theory of linear trellises," in *Information, Coding and Mathematics*, M. Blaum, P. G. Farrel, and H. C. A. van Tilborg, Eds. Boston, MA: Kluwer, pp. 323-354, May 2002.
- [14] R. Koetter and A. Vardy, "Construction of minimal tail-biting trellises," in *Proc. IEEE Workshop on Information Theory*, Killarney, Ireland, June 1998, pp. 72-74.
- [15] F. R. Kschischang and V. Sorokine, "On the trellis structure of block codes," *IEEE Trans. Inf. Theory*, vol. 41, pp. 1924-1937, Nov. 1995.
- [16] F. R. Kschischang, "The trellis structure of maximal fixed-cost codes," *IEEE Trans. Inf. Theory*, vol. 42, pp. 1828-1838, Nov. 1996.
- [17] D. J. Muder, "Minimal trellises for block codes," *IEEE Trans. Inf. Theory*, vol. 34, pp. 1049-1053, Sept. 1988.
- [18] A. R. Calderbank, G. D. Forney, Jr., and A. Vary, "Minimal tail-biting trellises: The Golay code and more," *IEEE Trans. Inf. Theory*, vol. 45, pp. 1435-1455, July 1999.
- [19] A. Vardy, "Trellis structure of codes," in *Handbook of coding theory*, V. S. Pless and W. C. Huffman, Eds. Amsterdam, The Netherlands: Elsevier, 1998, pp. 1989-2118.
- [20] V. Vazirani, H. Saran and B. Rajan, "An efficient algorithm for constructing minimal trellises for codes over finite abelian groups," *IEEE Trans. Inf. Theory*, vol. 42, pp. 1839-1854, Nov. 1996.
- [21] R. J. McEliece, "On the BCJR trellis for linear block codes," *IEEE Trans. Inf. Theory*, vol. 42, pp. 1072-1092, July 1996.
- [22] S. Lin and R. Y. Shao, "General structure and construction of tail-biting trellises for linear block codes," in *Pro. IEEE Int. Symp. Information Theory*, Sorrento, Italy, June 2000, p. 117.
- [23] I. Bocharova, R. Johannesson, B. Kudryashov, and P. Ståhl, "Tail-biting codes: Bounds and search results," *IEEE Trans. Inf. Theory*, vol. 48, pp. 137-148, Jan. 2002.
- [24] Y. Shany, Y. Be'ery, "linear tail-biting trellises, the square root bound, and applications for Reed-Muller codes," *IEEE Trans. Inf. Theory*, vol. 46, pp. 1514-1523, July 2000.
- [25] H. Kan and H. Shen, "Trellis properties of group codes," in *The 6th International Conference Advanced Communication Technology*, Vol. 1, 2004, pp. 203-206.
- [26] J. H. Conway and N. J. A. Sloane, *Sphere Packings, Lattices, and Groups*. New York: Springer-Verlag, 1988.
- [27] G. D. Forney, "Coset codes—Part II: Binary lattices and related codes," *IEEE Trans. Inf. Theory*, vol. IT-34, no. 5, pp. 1152-1187, Sept. 1988.
- [28] A. R. Hammons, P. V. Kumar, A. R. Calderbank, N. J. A. Sloane, and P. Solé, "The Z_4 -linearity of Kerdock, Preparata, Goethals and related codes," *IEEE Trans. Inf. Theory*, vol. 40, pp. 301-319, Mar. 1994.
- [29] F. J. MacWilliams and N. J. A. Sloane, *The Theory of Error-Correcting Codes*. New York: North-Holland, 1977.
- [30] H. Kan, X. Li and H. Shen, "The characteristic generators for a group code," *IEICE Trans. Fundamentals*, Vol. E89-A, no. 5, pp. 1513 - 1517, May 2006.